

# KONA Mega IoT Gateway

## High Capacity LoRaWAN® for Wide Area Deployments

The **KONA Mega IoT Gateway** provides network operators with a carrier grade product for the deployment of LoRaWAN® Internet of Things networks. The Gateway enables massive scalability in a compact form factor by supporting up to 12 million messages per day.

- Region Wide Network Coverage
- High Density Networks
- Smart Utilities
- Smart Cities
- Industrial Oil & Gas
- Commercial Farming
- Remote Monitoring
- Remote Asset Tracking



### Key Product Differentiators

- » High availability carrier grade design with support of in-service configuration and software updates.
- » Environmentally hardened aluminium enclosure fully tested to withstand extreme temperature conditions.
- » Full duplex operation making all receive and transmit channels available simultaneously.
- » Excellent isolation between the Tx and Rx bands as well as out of band rejection of Cellular and Paging networks.
- » Day-One scalability with support of up to 12 million received messages per day.
- » Easy to deploy supporting different backhaul and power options.
- » Fully integrated with the broader eco-system of LoRa™ network servers and sensors.

### Key Features

- » US915 ISM Band
- » Frequency Duplex 64+8 Rx / 4 Tx
- » Dual Antenna Support for Rx Diversity
- » Double Simultaneous Tx Channels
- » Integrated Cellular 3G/4G Modem
- » Copper and Optical Ethernet Backhaul
- » IP67 Design
- » Hardened Carrier Grade Enclosure
- » 1 Watt (2 x 27 dBm) Tx Power
- » High Linearity LNA/Receiver
- » Integrated Cavity Filter
- » Precise Network Synchronization (GPS)
- » Integrated GPS Holdover
- » Geolocation Support

# Kona Mega IoT Gateway

## High Capacity LoRaWAN® for Wide Area Deployments

### Technical and Functional System Specifications

#### Mechanical Parameters

MTBF	450,000 hours
DC Power Consumption	20 W (Typical)
Operational Temperature	-40°C to +60°C
Operational Humidity	10% to 100% Condensing
Ingress Protection	IP67
Size	222.2 x 267.6 x 101 mm
Weight	5 kg
Volume	5.9 L

#### LoRa Radio Parameters

ISM US915 Band	902 - 915 MHz (Rx)
	923 - 928 MHz (Tx)
Tx Power	1W (2 x 27 dBm)
Rx Sensitivity	-142 dBm (SF12, 293 bits/sec)
Rx Noise Figure	3.5 dB
Rx Linearity	-10 dBm
Rx Dynamic Range	70 dB Analog, 100+ dB Digital
Tx to Rx Isolation	75 dB

#### Software and Management

Tools	Access Control List management
	3G/4G Parameter Configuration
	System Health Monitor
	Flight Recorder
	Radio Configuration and Control
	Remote Software Upgrade
	Active and Passive image management
	Factory image provisioning
Networking	DHCPv4 client
	TFTP server
	HTTP server
	Firewall and Access Lists

#### Interfaces

Ethernet	RJ-45 & PoE (802.3bt)
GPS	N-Type
Cellular Backhaul (3G/4G)	N-Type (Optional)
Hybrid Optical and DC Power	Harting Hybrid (Optional)
LoRa Antenna (2 ports)	N-Type (2nd Port Optional)
Power	37-57 VDC or PoE++ (802.3bt)

#### Regulatory Compliance

Safety	UL / CSA / EN / IEC 62368-1
Regulatory	FCC: 15.247, 15.109, 15.209
	ISED: RSS - 247, RSS - Gen



TEKTELIC Communications is a premier supplier of best-in-class LoRaWAN® IoT Gateways, Sensors, and custom applications. These elements combined provide a powerful end-to-end solution that can be easily, quickly, and cost effectively deployed to address the most demanding IoT challenges.

For more information please visit [www.tektelic.com](http://www.tektelic.com)