



TECHNICAL SPECIFICATIONS

AirLink® RV50X



	North America & EMEA	Asia Pacific
LTE		
LTE CATEGORY	Cat 6	
Peak D/L	Up to 300 Mbps	
Peak U/L	Up to 50 Mbps	
4G LTE Frequency Bands*	2100(B1), 1900(B2), 1800(B3), AWS(B4), 850(B5), 2600(B7), 900(B8), 700(B12), 700(B13), 800(B20), 1900(B25), 850(B26), 700(B29), TDD B4 1	2100(B1), 1800(B3), 850(B5), 2600(B7), 900(B8), 850(B18), 850(B19), 1500(B21), 700(B28), TDD 38, TDD 39, TDD 40, TDD 41
3G HSPA/HSPA+ Frequency Bands*	2100(B1), 1900(B2), 1800(B3), AWS(B4), 850(B5), 900(B8)	2100(B1), 850(B5), 800(B6), 900(B8), 1700(B9), 850(B19),
3G TD-SCDMA Frequency Bands*		B39
APPROVALS		
Regulatory	FCC, IC, PTCRB, R&TTE, GCF, CE	RCM, JRF/JPA, Anatel
Carrier	Verizon, AT&T, T-Mobile USA, Southern Linc, Sprint, US Cellular, Rogers, Telus, Bell	Telstra
PART NUMBERS	1103052	1103045 1103973 (China)

*For carrier specific band support please refer to the hardware user guide.

	Specification
HOST INTERFACES	10/100/1000 Ethernet (RJ45) RS-232 serial port (DB-9) USB 2.0 Micro-B Connector 3 SMA antenna connectors (primary, diversity, GPS) Active GPS antenna support
INPUT/OUTPUT	Configurable I/O pin on power connector <ul style="list-style-type: none"> Digital Input ON Voltage: 2.7 to 36 VDC Configurable Pull-up for dry contact input Digital Open Collector Output > sinking 500 mA Analog Input: 0.5-36 VDC
LAN (ETHERNET/USB)	DNS, DNS Proxy DHCP Server IP Passthrough VLAN Host Interface Watchdog PPPoE
SERIAL	TCP/UDP PAD Mode Modbus (ASCII, RTU, Variable) PPP DNP3 Interoperability

	Specification
SATELLITE NAVIGATION (GNSS)	12 Channel GPS and GLONASS Receiver Acquisition Time: 1 s Hot Start Accuracy: <2 m (50%), <5 m (90%) Tracking Sensitivity: -145 dBm Reports: NMEA 0183 V3.0, TAIP, RAP, XORA Multiple Redundant Servers Reliable Store and Forward
NETWORK MANAGEMENT	Secure network management applications available in the cloud or licensed platform in the enterprise data center Fleet wide firmware upgrade delivery Router configuration and template management Router staging over the air and local Ethernet connection Over-the-air software and radio module firmware updates Device Configuration Templates Configurable monitoring and alerting Remote provisioning and airtime activation (where applicable)
GATEWAY MANAGEMENT INTERFACES	ALMS Local web user interface AT Command Line Interface (Telnet/SSH/Serial) SMS Commands SNMP

	Specification		Specification
NETWORK AND ROUTING	<ul style="list-style-type: none"> Network Address Translation (NAT) Port Forwarding Host Port Routing NEMO/DMNR VRRP Reliable Static Route Dynamic DNS Policy Routing Verizon ANTM IPv6 Gateway 	POWER	<ul style="list-style-type: none"> Input Voltage: 7 to 36 VDC LTE Idle Power: 900mW (75 mA @ 12VDC) Standby Mode Power: 53 mW (4.4 mA @ 12 VDC) triggered on low voltage, I/O or periodic timer Low voltage disconnect to prevent battery drain Built-in protection against voltage transients including 5 VDC engine cranking and +200 VDC load dump Ignition Sense with time delay shutdown Configurable features and ports to optimize power consumption
VPN	<ul style="list-style-type: none"> IPsec, GRE, and OpenVPN Client Up to 5 concurrent tunnels Split Tunnel Dead Peer Detection (DPD) Multiple Subnets 	ENVIRONMENTAL	<ul style="list-style-type: none"> Operating Temperature: -40°C to +70°C / -40°F to +158°F Storage Temperature: -40°C to +85°C / -40°F to +185°F Humidity: 90% RH @ 60°C Military Spec MIL-STD-810G conformance to shock, vibration, thermal shock, and humidity IP64 rated ingress protection
EVENTS ENGINE	<ul style="list-style-type: none"> Custom event triggers and reports Configurable interface, no programming Event Types: Digital Input, Network Parameters, Data Usage, Timer, Power, Device Temperature and Voltage Report Types: RAP, SMS, Email, SNMP Trap, TCP (Binary, XML, CSV) Event Actions: Drive Relay Output 	INDUSTRY CERTIFICATIONS	<ul style="list-style-type: none"> Safety: IECCE Certification Bodies Scheme (CB Scheme), UL 60950 Vehicle Usage: E-Mark (UN ECE Regulation 10.04), ISO7637-2, SAE J1455 (Shock & Vibration) Hazardous Environments: Class 1 Div 2 Environmental: RoHS, REACH, WEEE
DIMENSIONS	<ul style="list-style-type: none"> 119 mm x 34 mm x 85 mm (94 mm including connectors) 4.69 in x 1.34 in x 3.35 in (3.70 in including connectors) 	SUPPORT AND WARRANTY	<ul style="list-style-type: none"> Includes 1st Year AirLink Complete: <ul style="list-style-type: none"> AirLink Management Service (ALMS) Direct 24/7 Technical Support 3-year standard warranty; optional 2-year warranty extension 1-day Accelerated Hardware Replacement available through participating resellers
SECURITY	<ul style="list-style-type: none"> Remote Authentication (LDAP, RADIUS, TACACS+) DMZ Inbound and Outbound Port filtering Inbound and Outbound Trusted IP MAC Address Filtering PCI compatible 	ACCESSORIES	<ul style="list-style-type: none"> In the Box: DC Power Cable and Quick Start Guide Other Accessories (sold separately): <ul style="list-style-type: none"> 2000579 AC Adapter, 12VDC 6000659 DIN Rail Bracket For antenna options visit: sierrawireless.com/antennas
APPLICATION FRAMEWORK	<ul style="list-style-type: none"> ALEOS Application Framework (AAF) LUA Scripting Language Eclipse-based IDE Integrated with AirVantage® Dual-Core Processing 		

Related AirLink Products

AIRLINK DEVICE MANAGEMENT SOLUTIONS


AirLink Management Service (ALMS)



- Secure, Cloud-based network and asset management
- Remotely deploy, configure, monitor and manage AirLink devices
- Carrier-grade, high availability, secure, global infrastructure

AIRLINK VPN APPLIANCE

AirLink Connection Manager



- VPN appliance built from the ground up for AirLink routers & gateways
- Simplify deployment and management of your VPN solution, extending the enterprise to the network edge for fixed and mobile endpoints
- Carrier agnostic – ACM doesn't require fixed and/or public IP
- Compatible with FIPS 140-2, and always-on VPN capability

AIRLINK ANTENNA SOLUTIONS

AirLink Antennas



- Tested and certified to provide guaranteed performance with all AirLink routers and gateways
- Accelerate deployment with always-on, end-to-end connectivity

About Sierra Wireless

Sierra Wireless (NASDAQ: SWIR) (TSX: SW) is the leading IoT solutions provider that combines devices, network and software to unlock value in the connected economy. Companies globally are adopting IoT to improve operational efficiency, create better customer experiences, improve their business models and create new revenue streams. Whether it's a solution to help a business securely connect edge devices to the cloud, or a software/API solution to help manage processes associated with billions of connected assets, or a platform to extract real-time data to make the best business decisions, Sierra Wireless will work with you to create the right industry-specific solution for your next IoT endeavor. Sierra Wireless has more than 1,300 employees globally and operates R&D centers in North America, Europe and Asia.

For more information, visit www.sierrawireless.com.