



The AirLink LX60 provides LTE connectivity and Wi-Fi for primary and secondary/backup retail

## LX60 Product Description

The AirLink® LX60 LTE provides LTE connectivity and Wi-Fi for primary and secondary/backup retail applications including ATMs, kiosks and POS terminals. Also supports taxis and fleets.

### AIRLINK LX60 LTE

Cat-4 LTE router capable of 150 Mbps downlink and 50 Mbps uplink speeds.

## Ideal Applications

Primary or backup network connectivity for:

- Retail, Digital Signage
- POS
- Taxis and Commercial Fleets
- Small branch offices
- Industrial IoT
- Building automation

## Benefits

- Out-of-the box connectivity delivers same day operations
- Enables business continuity through simplified failover
- Connect virtually anywhere – without a need for wires or broadband
- Expand new services with global device connectivity
- Remote router management and comprehensive services through AirLink Complete

## LX60 Services and Support



### AIRLINK COMPLETE

Maximize your AirLink LX60 hardware investment with AirLink Complete – a comprehensive service package designed to empower you with the tools and support necessary to secure, optimize and effortlessly scale your LX60 deployments.

AirLink Complete includes\*:

- **AirLink Management Service (ALMS)** for remote device and security management
- **Expert technical support**
- **Extended hardware warranty** – up to 5 years maximum
- For more information on AirLink Complete visit our [web page](#)

*\*With active subscription. 1-year subscription included with the LX60 purchase*



### AIRLINK PREMIUM

Ideal for organizations managing mission-critical vehicle fleets, this service upgrade encompasses all the benefits of [AirLink Complete](#)\*, enhanced with:

- **Advanced Mobility Reporting\***: Offers comprehensive coverage and fleet reporting to monitor your network and vehicles.
- **Advance Replacement\***: Provides same-day shipping for in-warranty router replacements, minimizing downtime, spare inventory and keeping your operations running smoothly.

*\*With active subscription.*



### AIRLINK CONNECTION MANAGER (ACM) – [MOBILE VPN](#)

This purpose-built VPN solution securely extends your enterprise network to your AirLink router and its connected devices and applications.

Optimized for use in a mobile, multi-network environment, it seamlessly maintains VPN tunnels as users roam between multiple carrier and Wi-Fi networks to prevent downtime and loss of communications.

Available in a FIPS 140-2 compliant offering.



### ANTENNAS

- Tested and certified to provide guaranteed performance with all AirLink routers
- Accelerate deployment with always-on, end-to-end connectivity
- For more information on antennas specific to the LX60 router visit our [web page](#)

## AirLink LX60 – Router Specifications

CELLULAR		APPROVALS	
Peak D/L		Regulatory	
North America	Up to 150 Mbps, Cat-4 (WP7610)	North America	FCC, IC/ISED, PTCRB
EMEA	Up to 150 Mbps, Cat-4 (WP7607)	EMEA	GCF, CE
AU&NZ	Up to 150 Mbps, Cat-4 (WP7609)	AU&NZ	GCF, RCM
Peak U/L		Carrier	
North America	Up to 50 Mbps	North America	AT&T, Verizon, T-Mobile
EMEA	Up to 50 Mbps	PART NUMBERS	
AU&NZ	Up to 50 Mbps	North America	1104580, 1104572 (Wi-Fi + GNSS), 1104493 (Wi-Fi + GNSS + Telemetry)
4G LTE		EMEA	1104046, 1104047 (Wi-Fi + GNSS)
Frequency Bands		AU&NZ	1104048, 1104049 (Wi-Fi + GNSS)
North America	B2, B4, B5, B12, B13, B17, B66	HOST INTERFACES	
EMEA	B1, B3, B7, B8, B20, B28	2 Gigabit RJ-45 Ethernet ports RS-232 serial port (DB-9) USB 2.0 Micro-B Connector 3 SMA antenna connectors (cellular, diversity, GNSS) 1 RP SMA antenna connector (Wi-Fi) Active GNSS antenna support Aux Port (RS-485/GPIO)	
AU&NZ	B1, B3, B5, B7, B8, B28	SECURITY	
3G WCDMA/HSPA+		Remote Authentication (LDAP, RADIUS, TACACS+) DMZ Inbound and Outbound Port filtering Inbound and Outbound Trusted IP MAC Address Filtering Secure Firmware Update	
Frequency Bands			
North America	B2, B4, B5		
EMEA	B1, B8		
AU&NZ	B1, B5, B8		
2G GSM/GPRS			
EMEA	900, 1800		



## AirLink LX60 – Router Specifications

SATELLITE NAVIGATION GNSS (OPTIONAL)	
	Dedicated 48 channel GNSS Receiver supporting GPS, GLONASS, BeiDou, Galileo Tracking Sensitivity: -162 dBm Reports (Update Rate 1Hz): NMEA, TAIP Reliable Store and Forward via serial, TCP or UDP Inertial Navigation Sensors (Accelerometer and Gyro)
WI-FI (Optional)	
	Dual Band 2.4/5GHz Wi-Fi 802.11 b/g/n/ac (Wave2 Client Mode) Support for 10 clients, WPA2 Enterprise Output power 16dBm Access Point or Client Mode (Wi-Fi as WAN) Single SSID Support Captive Portal
LAN (ETHERNET/USB)	
	DHCP Server IP Passthrough VLAN Host Interface Watchdog PPPoE
ENVIRONMENTAL	
Temperature	<b>Operating Temperature:</b> -20°C to +65°C / -4°F to +149°F <b>Storage Temperature:</b> -40°C to +85°C / -40°F to +185°F Humidity: 90% RH @ 60°C
	Military Spec MIL-STD-810G conformance to shock, vibration, thermal shock, and humidity IP20 rated ingress protection
POWER	
Input/Operating Voltage	7 to 36 VDC
Power modes	Low voltage disconnect to prevent battery drain Built-in protection against voltage transients including 5 VDC engine cranking Ignition Sense with time delay shutdown
INPUT/OUTPUT	
	Configurable I/O (5 pins total) <ul style="list-style-type: none"> <li>5 Digital Inputs: ON Voltage: 2.7 to 36 VDC</li> <li>1 Digital Open Collector Output &gt; sinking 300 mA</li> <li>3 Analog Inputs: 0.5-5/0.5-10 VDC (range selectable)</li> <li>Configurable Pull-ups for dry contact input</li> </ul>
*For carrier specific band support please refer to the hardware user guide.	
SERIAL	
	TCP/UDP PAD Mode Modbus (ASCII, RTU, Variable) PPP DNP3 Interoperability
NETWORK AND ROUTING	
	Network Address Translation (NAT) Reliable Static Route Port Forwarding Dynamic DNS Policy Routing Verizon PNTM NEMO/DMNR IPV6 Gateway VRRP
VPN	
	IPsec, GRE, and OpenVPN Client Up to 5 concurrent tunnels Split Tunnel Dead Peer Detection (DPD)
ROUTER MANAGEMENT INTERFACES	
	Local web user interface AT Command Line Interface (Telnet/SSH/Serial) SNMP SMS Commands
APPLICATION FRAMEWORK	
	ALEOS Application Framework (AAF) Lua Scripting Language
EVENTS ENGINE	
	Custom event triggers and reports Configurable interface, no programming <b>Event Types:</b> Digital Input, Network Parameters, Data Usage, Timer, Power, Device Temperature and Voltage <b>Report Types:</b> RAP, SMS, Email, SNMP Trap, TCP (Binary, XML, CSV) <b>Event Actions:</b> Drive Relay Output
VEHICLE TELEMETRY	
	OBD II/ J1939 interface over serial (optional) Diagnostic real time alerts/reports (via AMM)
INDUSTRY CERTIFICATIONS	
Safety	IECE Certification Bodies Scheme (CB Scheme), UL 60950
Vehicle Usage	ISO7637-2, SAE J1455 (Shock, Vibration, Electrical)
Environmental	RoHS2, REACH, WEEE
Hazardous Environments	Class 1 Div 2 - Ambient temperatures of 0°C to +60°C



## AirLink LX60 – Router Specifications

AIRLINK COMPLETE (1 Year Included With Router Purchase)	
Support	24/7 technical support*
Hardware Warranty	1-year standard hardware warranty Extended hardware warranty up to 5 years with current subscription**
Device Management	AirLink Management Service (ALMS)*
Software Updates	Unrestricted critical firmware updates through at least December 31st, 2029
AIRLINK PREMIUM (Optional Upgrade)	
Includes All Airlink Complete Features* and Adds:	
Advanced Mobility Reporting	Coverage and fleet reporting***
Advance Replacement	Same-day shipping for in-warranty router replacements***

\*With current AirLink Complete subscription

\*\*Full warranty terms are available at [www.sierrawireless.com/end-user-warranty](http://www.sierrawireless.com/end-user-warranty)

\*\*\*With current AirLink Premium subscription

## ACCESSORIES

In the box	LX60, DC power cable, AirLink Complete leaflet and quick start guide. Other Accessories (sold separately):
	<ul style="list-style-type: none"> <li>• 2000579 AC Adapter, 12VDC</li> <li>• 6001214 DIN Rail Bracket</li> <li>• 6001004 I/O Cable</li> <li>• 6001110 Cellular Paddle Antenna</li> <li>• 6001111 Wi-Fi 2.4/5Hz Paddle Antenna</li> </ul>
	For Antenna options visit: <a href="http://Semtechwireless.com/antennas">Semtechwireless.com/antennas</a>
	For Telemetry Variant (1104493):
	6001204 OBD-II Y Cable
	6001192 J1939 Y Cable


## CONSTRUCTION

Polycarbonate housings that meet MIL-810/IP20 environmental standards.

## DIMENSIONS

146 mm x 42 mm x 100 mm (106 mm including connectors)  
5.74 in x 1.65 in x 3.93 in (4.17 in including connectors)  
Weight: 250g

## AirLink LX60 – Router Dimensions Diagram



**EBDS Wireless & Antennas**  
[www.ebds.eu](http://www.ebds.eu)  
 +33 (0)9 72 36 76 46

**About Semtech**

Semtech Corporation (Nasdaq: SMTC) is a high-performance semiconductor, IoT systems and cloud connectivity service provider dedicated to delivering high-quality technology solutions that enable a smarter, more connected and sustainable planet. Our global teams are committed to empowering solution architects and application developers to develop breakthrough products for the infrastructure, industrial and consumer markets.

To learn more about Semtech technology, visit us at [Semtech.com](http://Semtech.com) or follow us on [LinkedIn](#) or [X](#).

"Semtech", "Sierra Wireless" and "AirLink" are registered trademarks of Semtech Corporation or its subsidiaries. Other product or service names mentioned herein may be the trademarks of their respective owners. © 2023 Sierra Wireless, Inc. © 2024 Semtech Corporation. All rights reserved. 2024.08.05